




Water & Oil repellent, Very flexible and soft, cut level C, 15 gauge, double nitrile

KEY FEATURES

- Water and oil repellent, cut protection level C
- Thanks to high quality materials and Xcellent technology, it is very flexible, soft and comfortable
- Less hand fatigue while working
- Sandy finish provides super grip in oily and dry working condition
- Contact heat protection up to 100 °C according to EN407



PRODUCT DETAILS

Liner	UHMWPE mixed with other yarns
Gauge	15
Coating	Nitrile
Finishing	Flat & Sandy
Colour	Dark Blue / Black & Grey
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose or works with high cut hazard or contact heat hazard in oily or wet conditions.

Such as oil or fluids or other liquid (not chemicals) change, equipment maintenance, recycling, press shop works, inspection, assembly, sheet metal work, work with sharp or rough edge parts...



CERTIFICATION

CE EN21420:2020

Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to max. 5): **X**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **3**
Cut resistance from sharp objects EN ISO
13997:1999 (min. A to max. F, X - not tested): **C**
Impact protection (P if pass, F if failed): **-**

EN388:2016



4X43C

EN407:2020 Heat protection: levels obtained in laboratory tests

A - Limited flame spread: X of 4
B - Contact heat: 1 of 4
C - Convective heat: X of 4
D - Radiant heat: X of 4
E - Small splashes of molten metal: X of 4
F - Large quantities of molten metal: X of 4

EN407:2020



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-902 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

